

INSTRUCTIONS FOR REPROGRAMMING R2LC/LCRU 2 CIRCUIT BOARDS TO RESTORE SOUND / LIGHT/ MOTION / SMOKE OPERATION

- STEP 1:** Move switch on locomotive from run to program.
STEP 2: Turn on Command Base.
STEP 3: Place locomotive on track, then turn on power to track.
STEP 4: Press "ENG" then input locomotive ID#. Press "SET".
 "AUX 1", then press the number on the keypad that corresponds to your locomotive. (See the chart below).
STEP 5: Turn off power to track, wait ten seconds.
STEP 6: Remove locomotive from track, move switch from program to run.
STEP 7: Place locomotive back on track. Turn power on to track. **STEP 8:**
 Press "ENG" and ID#, then operate as normal.

** REPROGRAMMING CODES **

Code	Engine and Functions
0	Steam with Signal Sounds
1	Diesel with Signal Sounds
2	Diesel with Cab Light and Signal Sounds
4	Steam with Smoke
5	Diesel with Strobe Light - GP-7, GP-9, GP-20
6	Diesel with Cab Light/PB-1, FT's, F-3's
8	All Diesels with Smoke
34	New 6-2800 Series Hudson and Pacifics, K-4, West Side Shay
36	Alco Pa's (New in 97) WP/NYC F-3 and Texas Special
60	SD-40 UP 6-18273
74	All Engines with Wireless Tether (except J1E & SF Warhorse see below)
75	Soo Line SD-60
740	J1E Hudson & SF Warhorse (both loco and tender must be on the track)
750	Con rail Dash 8, 1999 Centennial SD-40
760	BNSF Dash 9 (6-1 8235)

COURTESY OF "R & D LINES MODEL TRAIN REPAIRS"
 732-549-0188 (CELL)
 732-549-2478 (PHONE)
 WEBSITE: <http://bencar.freeyellow.com/index.html>

